

Spec Sheet for 7250 Deluxe Rebar Positioning Lanyard



Features:

- 9/32" Grade 80 chain has a tensile strength of 10,000lbs
- Double-swivel rebar hook as a 2.5" gate opening and bi-directional swivel
- Offset clevis hooks eliminate unnecessary parts and reduce weight

Material:	Finish / Style #:	Tested at:
2" Grade 80 Chain	8-6C Black	TS: 10,000lbs
Offset Clevis Snaphook, Alloy Steel	YCM – Yellow Cadmium	TS: 5,000lbs
Double-swivel Rebar Hook	YCM – Yellow Cadmium	TS: 5,000lbs
Meets or exceeds applicable OSHA and ANSI standards including A10.32-2004		
Warning Labels		
Instructions		

Testing References:	
Chain:	ANSI A10.32 4.6.1.4
Shock Absorber:	Not Applicable
Snaphooks:	ANSI A10.32 4.5.2.2 / 4.5.3 / 4.5.5
Testing Procedure:	ANSI A10.32 7.1.1.4
Performance Rating:	<1,400lbs Max Arrest Force
Performance Rating:	5,000lbs Static Load

OSHA requires that the employer shall provide a training program for each employee who might be exposed to fall hazards. As part of the training program, the user of this product must:

- Become familiar with all instructions contained in the product manual
- Be trained in the correct use and care of their equipment
- Be aware of its application limitations
- Know and understand the consequences of improper use
- FAILURE TO FOLLOW INSTRUCTIONS MAY RESULT IN SERIOUS INJURY OR DEATH